

# Lifeguard Fluid 8

High Performance Oil for ZF Automatic Transmission

## Product description:

Lifeguard Fluid 8 has been specially developed for usage in 8HP automatic passenger car transmissions from ZF. The friction behavior has been optimally adapted for this transmission and is consistent over the entire service life. These features are a prerequisite for perfect shifting characteristics and vibration-free operation. Lifeguard Fluid 8 thus fulfills the most demanding requirements on the transmission's comfort behavior. The additives, which are customized to the individual components, also provide specialized protection and thus increase the service life of all transmission components. The optimized viscosity builds the foundation for maximized savings in fuel. The high-quality semi-synthetic base oil ensures that high thermal-oxidative stability is maintained throughout the transmission's entire service life. This product has a flat viscosity-temperature curve and is therefore perfectly suited for use in extremely cold or hot climates.



Order No.: 0671.090.312



Order No.: 0671.090.314

# Technical Data Sheet

## Product code:

0671.090.312 (1L)

0671.090.314 (5L)

## Specifications:

BMW: 83222152426, 83222289720, 83222305397;

Chrysler: 68157995AA, 68218058AA, 68218925AA, 68218925GA;

Land Rover: LR023288;

VAG: G055162A2, G060162A1, G060162A2, G060162A6;

ZF: S671090310, S671090311, S671090312, S671090313;

## Characteristics:

Color Green

Density at 15°C 846 kg/m<sup>3</sup>

Viscosity at 40°C 26 mm<sup>2</sup>/s

Viscosity at 100°C 5.6 mm<sup>2</sup>/s

Brookfield viscosity at -40°C 8850 mPa.s

Pour point -42°C

Flash point (COC) 206°C